

Buy A 1" IMPACT WRENCH

and Receive 20% OFF Standard Discount







(€

- D-Handle
- Inside and Outside Trigger
- Steel Anvil Housing
- Socket Retainer Style: Hole / Ring

Model Number	Drive Size		Bolt Cap Grade 5		Maximum Working Torque ¹		Maximum Torque		Blows Per Minute	Free Speed	Weight		Length		Side To Center		Avg Air Consumption	
	in	mm	in	mm	ft lb	Nm	ft lb	Nm	winute	rpm	lb	kg	in	mm	in	mm	cfm	l/s
D-Handle – Inside Trigger																		
IW1000MP-8H	1	25	1-1/4	32	1200	1630	1700	2300	825	6500	18.2	8.3	14.8	376	1.85	47	34	16
IW1000MP-8H5	1	25	1-1/4	32	1200	1630	1700	2300	825	6500	19.7	8.9	19.3	490	1.85	47	34	16
IW1000MP-8H8	1	25	1-1/4	32	1200	1630	1700	2300	825	6500	20.7	9.4	22.3	556	1.85	47	34	16

¹Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester. Air Inlet Size: 1/2* NPT • Recommended Hose Size: 1/2* (30 mm) • Performance rated @ 90 psig (6.2 bar) air pressure