

Buy Any SIOUX RIVET SHAVER

and Receive 20% OFF Standard Discount



RIVET SHAVERS

- 0.0005" Locking **Depth Increments**
- Spindle Lock
- SRS6P E-Z Set and Lock
- SRS10P Locking Collar with Reference Marks





Model Number	Cutter Diameter		Free Speed	Weight		Length		Side to Center		Maximum Air Consumption	
	in	mm	rpm	lb	kg	in	mm	in	mm	cfm	l/s
0.6 hp (0.45 kW) – Pi	stol Grip –	1/4"-28 Inte	ernal Thread								
SRS6P21-5	5/16	8	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-6	3/8	10	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-7	7/16	11	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-8	1/2	13	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-9	9/16	14	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-10	5/8	16	21000	2.0	0.9	6.5	165	0.8	21	25	12
SRS6P21-9W	9/16	14	21000	2.0	0.9	6.5	165	0.8	21	25	12
1 hp (0.75 kW) - Pist	tol Grip – 1/	4"-28 Inter	nal Thread								
SRS10P21-5	5/16	8	21000	2.7	1.2	8.0	205	0.9	23	25	12
SRS10P21-6	3/8	10	21000	2.7	1.2	8.0	205	0.9	23	25	12
SRS10P21-7	7/16	11	21000	2.7	1.2	8.0	205	0.9	23	25	12
SRS10P21-8	1/2	13	21000	2.7	1.2	8.0	205	0.9	23	25	12
SRS10P21-9	9/16	14	21000	2.7	1.2	8.0	205	0.9	23	25	12
SRS10P21-10	5/8	16	21000	2.7	1.2	8.0	205	0.9	23	25	12
1 hp (0.75 kW) – Inlir	1 hp (0.75 kW) – Inline – 1/4"-28 Internal Thread										
SRS10S21-8	1/2	13	21000	2.5	1.1	10.0	255	0.9	23	30	14

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Skirt • Comfort Grip (Pistol Grip models) Stabilizer (SRS10P) • Cutters Not Included

RIVET SHAVER SKIRTS AND STABILIZER

Part	Cutter Diameter					
Number	in	mm				
2925-5	5/16	8				
2925-6	3/8	10				
2925-7	7/16	11				
2925-8B	1/2	13				
2925-9	9/16	14				
2925-9W	9/16	14				
2925-10	5/8	16				





For Use On
SRS6P21 series